



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

SECTION 1. IDENTIFICATION

Product name : Valvoline™ Mercon V Automatic Transmission Fluid

Product code : 822345

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

Other hazards

None known.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	>= 15 - <= 40
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7*	>= 15 - <= 40
Distillates (petroleum), hydrotreated light paraffinic;	64742-55-8*	>= 3 - <= 7

Baseoil — unspecified		
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0*	$\geq 3 - \leq 7$
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	$\geq 1 - \leq 5$
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified	72623-87-1*	$\geq 1 - \leq 5$
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0*	$\geq 0.5 - \leq 1.5$
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	$\geq 45 - \leq 70$
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7*	$\geq 10 - \leq 30$
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	$\geq 3 - \leq 7$
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0*	$\geq 3 - \leq 7$
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	$\geq 1 - \leq 5$
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0*	$\geq 0.5 - \leq 1.5$

* Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and	: No symptoms known or expected.



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

delayed
Notes to physician : No hazards which require special first aid measures.
Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Hazardous combustion products : carbon dioxide and carbon monoxide

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: red
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 374 °F / 190 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.858 g/cm ³ (60.01 °F / 15.56 °C)
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Viscosity, dynamic	: No data available
Viscosity, kinematic	: 34.6 mm ² /s (104 °F / 40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
---------------------	-----------------------------



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 15 g/kg
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No skin irritation

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Species : Rabbit
Result : No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified due to lack of data.



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The toxicological data has been taken from products of similar composition.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Result : No eye irritation
Assessment : No eye irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No eye irritation

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Species : Rabbit
Result : No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The toxicological data has been taken from products of similar composition.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Result : No eye irritation
Assessment : No eye irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Result : Slight, transient irritation

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Result : No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Carcinogenicity - : Not classifiable as a human carcinogen.
Assessment

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated $\geq$ 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): $> 10,000$ mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): ≥ 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated $\geq$ 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n- : log Pow: Expected > 7
octanol/water

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n- : log Pow: Expected > 7
octanol/water

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological : No data available



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylene	1330-20-7	100	100 (F003)
ethylbenzene	100-41-4	100	100 (F003)
toluene	108-88-3	100	100 (F005)
benzene	71-43-2	10	10 (D018)

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

xylene	1330-20-7	>= 0 - < 0.1 %
ethylbenzene	100-41-4	>= 0 - < 0.1 %
toluene	108-88-3	>= 0 - < 0.1 %
propylene oxide	75-56-9	>= 0 - < 0.1 %
benzene	71-43-2	>= 0 - < 0.1 %
naphthalene	91-20-3	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

xylene	1330-20-7	>= 0 - < 0.1 %
ethylbenzene	100-41-4	>= 0 - < 0.1 %
toluene	108-88-3	>= 0 - < 0.1 %
propylene oxide	75-56-9	>= 0 - < 0.1 %
benzene	71-43-2	>= 0 - < 0.1 %
naphthalene	91-20-3	>= 0 - < 0.1 %

US State Regulations

Massachusetts Right To Know

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
ethyl acrylate	140-88-5

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated light paraffinic; Baseoil —	64742-55-8
---	------------



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

unspecified	
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7
PROPRIETARY OF 000000240135	Not Assigned
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4

Maine Chemicals of High Concern

ethylbenzene	100-41-4
toluene	108-88-3
benzene	71-43-2
naphthalene	91-20-3

Vermont Chemicals of High Concern

ethanediol	107-21-1
ethylbenzene	100-41-4
toluene	108-88-3
benzene	71-43-2
naphthalene	91-20-3
1,4-dioxane	123-91-1

Washington Chemicals of High Concern

ethanediol	107-21-1
ethylbenzene	100-41-4
toluene	108-88-3
benzene	71-43-2
naphthalene	91-20-3
1,4-dioxane	123-91-1

California Prop. 65

WARNING: This product can expose you to chemicals including ethyl acrylate, 2-ethylhexyl acrylate, ethylbenzene, propylene oxide, ethylene oxide, benzene, naphthalene, 1,4-dioxane, which is/are known to the State of California to cause cancer, and ethanediol, toluene, ethylene oxide, benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7
---	------------

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory



SAFETY DATA SHEET

Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information



SAFETY DATA SHEET


Valvoline™ Mercon V Automatic Transmission Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

NFPA 704:



HMIS® IV:

HEALTH	/	1
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -



SAFETY DATA SHEET
Valvoline™ Mercon V Automatic Transmission
Fluid

Version: 3.3

Revision Date: 03/28/2025

Print Date:
05/07/2025

Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Revision Date : 03/28/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0394062