

Section 1. Identification

Product name Castrol TranSynd 668
SDS # 470369
Code 470369-US65

Relevant identified uses of the substance or mixture and uses advised against

Product use Automatic transmission fluid.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: 1-888-CASTROL

EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735
Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

Section 2. Hazards identification

OSHA/HCS status This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Hazards not otherwise classified Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture Mixture
Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≥50 - ≤75	CAS: 72623-87-1
Distillates (petroleum), hydrotreated light paraffinic	≤3	CAS: 64742-55-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	CAS: 64742-65-0
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	≤3	CAS: 72623-86-0
Distillates (petroleum), solvent-refined heavy paraffinic	≤3	CAS: 64741-88-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Distillates (petroleum), hydrotreated light paraffinic	None. OSHA PEL (United States) [Oil mist, mineral] TWA 8 hours: 5 mg/m ³ . Issued/Revised: 6/1993. ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m ³ . Form: Inhalable

Section 8. Exposure controls/personal protection

Distillates (petroleum), solvent-dewaxed heavy paraffinic	fraction. Issued/Revised: 11/2009. OSHA PEL (United States) [Oil mist, mineral] TWA 8 hours: 5 mg/m ³ . Issued/Revised: 6/1993. ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction. Issued/Revised: 11/2009.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OSHA PEL (United States) [Oil mist, mineral] TWA 8 hours: 5 mg/m ³ . Issued/Revised: 6/1993. ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction. Issued/Revised: 11/2009.
Distillates (petroleum), solvent-refined heavy paraffinic	OSHA PEL (United States) [Oil mist, mineral] TWA 8 hours: 5 mg/m ³ . Issued/Revised: 6/1993. ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction. Issued/Revised: 11/2009.

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Section 8. Exposure controls/personal protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Color

Red.

Odor

Not available.

Odor threshold

Not available.

pH

Not applicable.

Melting point/freezing point

Not available.

Boiling point or initial boiling point and boiling range

Not available.

Flash point

Open cup: >210°C (>410°F) [Cleveland ASTM D 92]

Pour point

-51 °C

Evaporation rate

Not available.

Flammability

Not available.

Lower and upper explosion limit/flammability limit

Not available.

Vapor pressure

Ingredient name	Vapor Pressure at 20 °C			Vapor pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191			

Section 9. Physical and chemical properties

Lubricating oils
(petroleum), C15-30,
hydrotreated neutral oil-
based

<0.07501

<0.01

ASTM D 5191

Distillates (petroleum),
solvent-refined heavy
paraffinic

<0.07501

<0.01

ASTM D 5191

Relative vapor density

Not available.

Density

<1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

**Partition coefficient: n-
octanol/water**

Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

Decomposition temperature

Not available.

Viscosity

Kinematic: 33 mm²/s (33 cSt) at 40°C

Kinematic: 6.5 to 7.5 mm²/s (6.5 to 7.5 cSt) at 100°C

Particle characteristics

Median particle size

Not applicable.

Section 10. Stability and reactivity

Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability

The product is stable.

**Possibility of hazardous
reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition
products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Lubricating oils (petroleum), C20-50,
hydrotreated neutral oil-based

Result

Rat - Oral - LD50

>5000 mg/kg
OECD 423

Rat - Dermal - LD50

>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours]
OECD 403

Distillates (petroleum), hydrotreated light
paraffinic

Rat - Oral - LD50

Product name Castrol TranSynd 668

Product code 470369-US65

Page: 6/14

Version 2.07 **Date of issue** 11/16/2025.

Format US

Language ENGLISH

Section 11. Toxicological information

Distillates (petroleum), solvent-dewaxed heavy paraffinic

>5000 mg/kg
OECD 401
Rabbit - Dermal - LD50
>5000 mg/kg
OECD 402
Rat - Inhalation - LC50 Dusts and mists
>5.53 mg/l [4 hours]
OECD 403
Rat - Oral - LD50
>5000 mg/kg
OECD 401
Rat - Dermal - LD50
>2000 mg/kg
OECD 402
Rat - Inhalation - LC50 Dusts and mists
>5.53 mg/l [4 hours]
OECD 403
Rat - Oral - LD50
>5000 mg/kg
OECD 401
Rat - Dermal - LD50
>2000 mg/kg
OECD 402
Rat - Inhalation - LC50 Dusts and mists
>5 mg/l [4 hours]
OECD 403

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Skin corrosion/irritation

Product/ingredient name

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed heavy paraffinic
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Result

Rabbit - Skin - Non-irritant to skin.
OECD 404
Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.
OECD 404

Serious eye damage/eye irritation

Product/ingredient name

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed heavy paraffinic
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Result

Rabbit - Eyes - Severe irritant
OECD 405
Rabbit - Eyes - Non-irritating to the eyes.
OECD 405
Rabbit - Eyes - Non-irritating to the eyes.
OECD 405
Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

Result

Section 11. Toxicological information

Lubricating oils (petroleum), C20-50,
hydrotreated neutral oil-based

Distillates (petroleum), hydrotreated light
paraffinic

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Lubricating oils (petroleum), C15-30,
hydrotreated neutral oil-based

Guinea pig - skin

OECD 406

Result: Not sensitizing

Guinea pig - skin

OECD 406

Result: Not sensitizing

Guinea pig - skin

OECD 406

Result: Not sensitizing

Guinea pig - skin

OECD 406

Result: Not sensitizing

Germ cell mutagenicity

Product/ingredient name

Lubricating oils (petroleum), C20-50,
hydrotreated neutral oil-based

Result

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Positive

In vivo - Mammal - species unspecified

OECD [Mammalian Erythrocyte Micronucleus Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Cell Gene Mutation Test]

Result: Negative

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

In vitro - Unspecified

OECD [In vitro Mammalian Cell Gene Mutation Test]

Result: Negative

In vivo - Mammal - species unspecified

OECD [Mammalian Erythrocyte Micronucleus Test]

Result: Negative

Distillates (petroleum), hydrotreated light
paraffinic

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Lubricating oils (petroleum), C15-30,
hydrotreated neutral oil-based

Carcinogenicity

Product/ingredient name

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Result

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Section 11. Toxicological information

Not available.

Reproductive toxicity

Product/ingredient name

Lubricating oils (petroleum), C20-50,
hydrotreated neutral oil-based

Distillates (petroleum), hydrotreated light
paraffinic

Distillates (petroleum), solvent-dewaxed
heavy paraffinic

Result

Rat - Oral

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Rat - Oral

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Rat - Oral

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name

Lubricating oils (petroleum), C20-50,
hydrotreated neutral oil-based
Distillates (petroleum), hydrotreated light
paraffinic
Lubricating oils (petroleum), C15-30,
hydrotreated neutral oil-based

Result

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

No known significant effects or critical hazards.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

No specific data.

Inhalation

May be harmful by inhalation if exposure to vapor, mists or fumes resulting from thermal decomposition products occurs.

Skin contact

Adverse symptoms may include the following:
irritation
dryness
cracking

Section 11. Toxicological information

Ingestion No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects Not available.

Potential delayed effects Not available.

Long term exposure

Potential immediate effects Not available.

Potential delayed effects Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] Not available.

General No known significant effects or critical hazards.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Product/ingredient name

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Distillates (petroleum), hydrotreated light paraffinic

Result

Acute - NOEL

OECD 201
Algae
≥100 mg/l [72 hours]

Acute - EL50

OECD 202
Daphnia
>10000 mg/l [48 hours]

Acute - LL50

OECD 203
Fish
>100 mg/l [96 hours]

Chronic - NOEL

OECD 211
Daphnia
≥1000 mg/l [21 days]

Acute - EL50

OECD 201
Algae
>100 mg/l [72 hours]

Acute - EL50

OECD 202
Daphnia

Section 12. Ecological information

Distillates (petroleum), solvent-dewaxed heavy paraffinic	>10000 mg/l [48 hours]
	Acute - LL50
	OECD 203
	Fish
	>100 mg/l [96 hours]
	Chronic - NOEL
	OECD 201
	Algae
	≥100 mg/l [72 hours]
	Chronic - NOEL
	OECD 211
	Daphnia
	10 mg/l [21 days]
	Acute - EL50
	OECD 201
	Algae
	>100 mg/l [72 hours]
	Acute - EL50
	OECD 202
	Daphnia
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	>10000 mg/l [48 hours]
	Acute - LL50
	OECD 203
	Fish
	>100 mg/l [96 hours]
	Chronic - NOEL
	OECD 201
	Algae
	≥100 mg/l [72 hours]
	Chronic - NOEL
	OECD 211
	Daphnia
	10 mg/l [21 days]
	Acute - ErL50
	OECD 201
	Algae
	100 mg/l [72 hours]
	Chronic - NOELR
	OECD 201
	Algae
	100 mg/l [72 hours]
	Acute - EL50
	OECD 202
	Daphnia
	>1000 mg/l [48 hours]
	Chronic - NOELR
	OECD 211
	Daphnia
	10 to 1000 mg/l [21 days]
	Acute - LL50
	OECD 203
	Fish
	>100 mg/l [96 hours]

Persistence and degradability

Not expected to be rapidly degradable.

Product/ingredient name	Result
-------------------------	--------

Section 12. Ecological information

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 301F 31% [28 days] - Inherent
Distillates (petroleum), hydrotreated light paraffinic	OECD 301F 31% [28 days] - Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F 31% [28 days] - Not readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Distillates (petroleum), solvent-refined heavy paraffinic	3.9 to 6	-	High

Mobility in soil

Soil/Water partition coefficient Not available.

Mobility Spillages may penetrate the soil causing ground water contamination.

Other adverse effects No known significant effects or critical hazards.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Section 14. Transport information

[Transport in bulk according to IMO instruments](#) Not available.

Section 15. Regulatory information

U.S. Federal regulations

[United States inventory \(TSCA 8b\)](#) All components are active or exempted.

[TSCA 12\(b\) - Chemical export notification](#)

Not applicable.

[SARA 302/304](#)

[Composition/information on ingredients](#)

No products were found.

[SARA 311/312](#)

[Classification](#) Not applicable.

[SARA 313](#)

[Form R - Reporting requirements](#) This product does not contain any hazardous ingredients at or above regulated thresholds.

[Supplier notification](#) This product does not contain any hazardous ingredients at or above regulated thresholds.

[State regulations](#)

[Massachusetts](#)

The following components are listed: OIL MIST, MINERAL; MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC; OIL MIST, MINERAL; OIL MIST, MINERAL; OIL MIST, MINERAL

[New Jersey](#)

The following components are listed: MINERAL OIL (UNTREATED and MILDLY TREATED); Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated

[Pennsylvania](#)

The following components are listed: Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated

[California Prop. 65](#)

 **WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including sulfur dioxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

[Other regulations](#)

[Australia inventory \(AIC\)](#) All components are listed or exempted.

[Canada inventory](#) All components are listed or exempted.

[China inventory \(IECSC\)](#) All components are listed or exempted.

[Japan inventory \(CSCL\)](#) All components are listed or exempted.

[Korea inventory \(KECI\)](#) All components are listed or exempted.

[Philippines inventory \(PICCS\)](#) All components are listed or exempted.

[Taiwan Chemical Substances Inventory \(TCSI\)](#) All components are listed or exempted.

[REACH Status](#) For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

[National Fire Protection Association \(U.S.A.\)](#)



History

Date of issue/Date of revision	11/16/2025.
Date of previous issue	10/27/2025.
Prepared by	Product Stewardship
Key to abbreviations	ACGIH = American Conference of Industrial Hygienists ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS Number = Chemical Abstracts Service Registry Number GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OEL = Occupational Exposure Limit SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average UN = United Nations UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.